

**Continental
Belton**

MOHAWK

HOLLY MFG.

HV HAYV

Mfg By: AG-Meier Industries, L

MOHAWK

MANUFACTURED BY
AG-MEIER IND. L.L.C.
(254) 939-3731
1-800-446-7319

Brave Rotary Cutters



	BRAVE 4	BRAVE 5	BRAVE 6	BRAVE 7
Cutting Height	1"-15"	1"-15"	1"-15"	1"-15"
Cutting Width	48"	60"	72"	82-1/2"
Overall Width	53-3/4"	66-1/2"	79"	85-1/2"
Overall Length	75"	96"	110"	120"
Approx. Weight	460 lbs.	555 lbs.	645 lbs.	1,055 lbs.
Blades	1/2" x 3"	1/2" x 3"	1/2" x 3-1/2"	1/2" x 4"
Blade Carrier	Dish	Dish	Dish	Dish
Blade Tip Speed (fpm)	9,992	12,490	14,989	14,394

Max. Brush Size	1-1/2"	1-1/2"	1-1/2"	2"
Gearbox HP	45	45	45	80
Gearbox Protection	Shear Pin (Slip Clutch Optional)			Slip Clutch
Drive Line Size #	Series 4	Series 4	Series 4	Series 6
Deck Thickness (Ga)	11	11	11	10
Side Skirt Thickness (Ga)	11	11	11	7
Side Skirt Depth	7"	7"	7"	8"
Wheels	Laminated Tires	Laminated Tires	Laminated Tires	Laminated Tires
Number of Wheels	1	1	1	2
Hitch Type	3 Pt., Cat. I	3 Pt., Cat. I	3 Pt., Cat. I	3 Pt., Cat. 2
Tractor P.T.O. RPM	540	540	540	540
Minimum HP Required	20	25	30	40
Taper Splined Output Shaft Dia	1-5/8"	1-5/8"	1-5/8"	2"
Safety Shield	Rubber Deflectors or Chain Guards			